

LIFEPAK® CR-T AUTOMATED EXTERNAL DEFIBRILLATOR TRAINING SYSTEM

- Dynamic and versatile training tool
- Simulates the LIFEPAK CR® Plus AED in appearance and operation
- Low operating cost
- Incorporates scenarios from the American Heart Association's HeartSaver AED course and the American Red Cross CPR/AED courses
- Same intuitive and simple operation as the LIFEPAK CR Plus AED
- A wireless remote control enables flexible, dynamic custom training scenarios



The LIFEPAK CR-T AED Training System provides realistic training in the use of the LIFEPAK CR Plus defibrillator without the actual charge and discharge of electrical energy.

The *CR-T* mimics the appearance of the *CR Plus* and simulates actual operations of the *CR Plus*. The *CR-T* follows the simple operation of the *CR Plus* and guides users through simulated analysis, energy delivery and prompted CPR intervals. All of its functions are programmable to simulate the full range of scenarios possible during "real life" use of the LIFEPAK CR Plus defibrillator.

The *CR-T* enables you to run preconfigured training scenarios and to create dynamic custom scenarios of your own. Using a wireless remote control, you can interrupt preconfigured routines to simulate events such as patient motion or electrode

disconnection. The *CR-T* is a cost-effective training solution. It is powered by four standard D-cell batteries. The electrodes are affordable and reusable, and mimic the rapid access QUIK-PAK™ pacing/defibrillation ECG electrodes unique to the LIFEPAK CR Plus defibrillator.

The *CR-T* provides realistic and versatile training for all skill levels. It is designed to meet the needs of all trainers, for teaching both first time lay users and refreshing experienced emergency responders.

The LIFEPAK CR-T AED Training System: realistic, versatile, dynamic, easy to use, and developed by trainers for trainers.

SPECIFICATIONS

GENERAL

Device designed for low impact, low stress environments. For use in temperature controlled areas protected from precipitation. Capable of withstanding heavy usage and prolonged periods of operation.

Physical Characteristics:

Height : 10.7 cm (4.2 in)

Width : 20.3 cm (8.0 in)

Depth : 24.1 cm (9.5 in), excluding handle

Weight : 1.9 kg (4.1 lb), with batteries

Batteries: 6 volts/4 cells, range 3.4–6.5 Vdc. Four nonchargeable D-cell alkaline batteries. New batteries will provide not less than 100 hours of continuous operation under normal, indoor-environment conditions.

Buttons: Master ON/OFF, Lid Release/ON-OFF and SHOCK.

Displays

OK Indicator: Simulates an indicated OK status.

Charge-Pak Indicator: When displayed, simulates a need to replace CHARGE-PAK™ battery charger.

Service Indicator: Simulates that service is required.

Operating Temperature: 3° to 38° C (37° to 100° F)

Storage Temperature: -10° to 60° C (14° to 140° F). Remove batteries for storage.

Water Resistance: Spill resistant per IEC 60601-1, part 44.3.

REMOTE CONTROL

Transmission: Wireless infrared signal. Range: 3 meters (10 ft) maximum. 82 in (2 meter) optional cable attachment.

Size: 4.57 cm x 8.4 cm x 1.6 cm (1.8 in x 3.3 in x .6 in)

Weight (without batteries): 36 gm

Batteries: 3 volts supplied by two AAA alkaline batteries.

Buttons: 13-key membrane switch pad labeled for the following functions: NO SHOCK, SERVICE REQUIRED, ELECTRODE PAD CONTACT, MOTION, REPLACE CHARGE-PAK, LOW INTERNAL BATTERY, CPSS, PAUSE, VOLUME CONTROL, SETUP NAVIGATION BUTTONS.

Operating Temperature: 3° to 38° C (37° to 100° F)

Storage Temperature: -10° to 60° C (14° to 140° F). Remove batteries for storage.

Water Resistance: Spill resistant per IEC 60601-1, part 44.3.

For further information, please contact Physio-Control at 800.442.1142 (U.S.), 800.895.5896 (Canada) or visit our website at www.physio-control.com



Physio-Control Headquarters

11811 Willows Road NE
Redmond, WA 98052
www.physio-control.com

Customer Support

P. O. Box 97006
Redmond, WA 98073
Toll free 800 442 1142
Fax 800 426 8049

Physio-Control Canada

Physio-Control Canada Sales, Ltd.
7111 Syntex Drive, 3rd Floor
Mississauga, ON
L5N 8C3
Canada
Toll free 800 895 5896
Fax 866 430 6115



Physio-Control, Inc., 11811 Willows Road NE, Redmond, WA 98052 USA